



Screw Compressor APS 10DD IVR Combi Dry 13 bar 10 hp/7.5 kW 270-1258 l/min 500 l

Product Images



Additional Information

SKU	36212-DD
EAN	08712418359725
Length (mm)	1935
Width (mm)	655
Height (mm)	1665
Weight (kg)	427.000000
Workload (labor/rest %)	100/0
Motor power (hp / kW)	10.0 HP / 7.5 kW
Motor efficiency class	IE3
Motor Type	PM Synchroon Motor
Drive	Direct driven 1:1
Control panel	ES 4000 STANDARD
Dryer	Yes
Dryer voltage (V)	230
Air receiver	Yes
Capacity air receiver (l)	500
Galvanized tank	No
Maximum pressure (bar)	13
Minimum free air delivery (l/min)	270
Minimum free air delivery (m3/h)	16.2
Maximum free air delivery (l/min)	1258
Maximum free air delivery (m3/h)	75.48
Noise level dB(A) (0 m)	64
Noise level dB(A) (4 m)	44
Cut-in pressure (bar)	5.5
Plug type	EU

Refrigerant	R134a
Main air connection (")	3/4
Minimum ambient temperature (°C)	5
Maximum ambient temperature (°C)	46
Oilfree	No
Oil capacity (l)	4
Air-end	C55*
Stages	1
Start	Inverter
Voltage (V)	400 V / 50 Hz / 3 Ph
Variable speed (IVR)	Yes
Minimum rpm 10 bar (rpm)	1241
Maximum rpm 10 bar (rpm/Hz)	5023

