



# Compressor HK 425-50 Pro 10 bar 3 hp/2.2 kW 317 l/min 50 l

## Product Images



## Additional Information

---

SKU	360533
EAN	8712418361582
Length (mm)	780
Width (mm)	410
Height (mm)	740
Weight (kg)	53.000000
Workload (labor/rest %)	50/50
Start	Direct
Drive	V-belt driven
Belt size	A48 (1219)
Flywheel diameter (mm)	320
Pulley diameter (mm)	110
Cylinders	2
Voltage (V)	400 V / 50 Hz / 3 Ph
Air receiver	Yes
Capacity air receiver (l)	50
Galvanized tank	No
Intake capacity (l/min)	400
Free air delivery (l/min)	317
Free air delivery (m3/h)	19.02
Cut-in pressure (bar)	8
Maximum pressure (bar)	10
Noise level dB(A) (0 m)	94
Noise level dB(A) (4 m)	74
Noise level dB(A) (7 m)	69
Sound volume reduction	No

Main air connection (")	1/2
Connection type	Universal + Euro
Number of couplings air connections	1 - 2
Number of reducable couplings air connections	1
Stages	1
Oilfree	No
Filter with reducer	No
Pump speed (RPM)	1250
Motor power (hp / kW)	3.0 HP / 2.2 kW
Wheels	Yes
Pump type	K17C
Intercooler	No
After cooler	Yes

