



# Screw Compressor APS 10 IVR X 10 bar 10 hp/7.5 kW 270-1020 l/min

369410-IVR



## Product details

SKU	369410-IVR
EAN	08712418372298
Length (mm)	910
Width (mm)	700
Height (mm)	925
Weight (kg)	200.000000
Workload (labor/rest %)	100/0
Motor power (hp / kW)	10.0 HP / 7.5 kW
Motor efficiency class	IE3
Motor Type	PM Synchroon Motor
Motor protection class	IP55
Drive	Direct driven 1:1
Control panel	MAM-6080
Available languages	English, Dutch, Polish, German
Dryer	No
Air receiver	No
Galvanized tank	No
Maximum pressure (bar)	10
Free air delivery at 8 bar (l/min)	1020
Free air delivery at 10 bar (l/min)	950
Minimum free air delivery (l/min)	270
Minimum free air delivery (m3/h)	16.2
Maximum free air delivery (l/min)	1020
Maximum free air delivery (m3/h)	61.2
Noise level dB(A) (0 m)	63
Noise level dB(A) (4 m)	43

Cut-in pressure (bar)	6
Plug type	EU
Cooling air volume (m3/h)	2300
Main air connection (")	3/4
Minimum ambient temperature (°C)	10
Maximum ambient temperature (°C)	45
Oilfree	No
Oil capacity (l)	6
Stages	1
Start	Inverter
Voltage (V)	400 V / 50 Hz / 3 Ph
Variable speed (IVR)	Yes
Minimum rpm 10 bar (rpm)	1220
Maximum rpm 10 bar (rpm/Hz)	2700
Minimum energy consumption 10 bar (kW/m3/h)	9.2
Maximum energy consumption 10 bar (kW/m3/h)	12.1

## Description

A compressor with great qualities and characteristics. This 7.5 kW, directly driven screw compressor has the latest technologies. For example, this machine has a Permanent Magnet motor for optimum energy saving (up to 8% higher than a standard Asynchronous motor) and the compressor has a wifi module to be able to monitor and adjust the compressor remotely. The yield is a maximum of 1020 liters per minute. All parameters can be read and adjusted in the menu of the very comprehensive but well-arranged controller which is equipped with a full color touchscreen. With this, every APS 10 X IVR can be adjusted per situation for maximum efficiency. All components are easily accessible when the panels are removed during maintenance. The machine has been carefully designed so that fewer parts are maintenance-sensitive. The service interval of 3,000 hours also ensures lower maintenance costs. This machine is very suitable for small businesses to medium-sized businesses such as garage companies.

### X series Screw compressors

By continuously investing in the development of our products, the Airpress Group presents a new series of screw compressors. The screw compressors are available from 5.5 kW to 37 kW. The APS X series is available in two versions: controlled at a fixed speed or speed. Machines of 15 kW are also available with a two-stage screw block. These versions have an increased performance with the same power consumption as a single-stage version. Depending on demand, these machines are available as a separate unit, mounted

on a tank or mounted on a tank and equipped with a compressed air dryer. Compressors of the X series are characterized by a new generation of screw blocks. The direct drive avoids losses due to the transmission. Reliable and efficient, easy-to-use screw compressors ensure trouble-free operation at minimal costs. Equipped with a modern control panel, you can constantly monitor the screw compressor and change parameters if necessary.

