



# Thread locker adhesive Ultra Strength 50ml

## Product Images



## Additional Information

|                      |               |
|----------------------|---------------|
| SKU                  | 4306545       |
| EAN                  | 8712418397086 |
| Weight (kg)          | 0.070000      |
| Safety standard      | No            |
| Rotatable            | No            |
| Hardened             | No            |
| Condensate separator | No            |
| Flow regulator       | No            |
| Capacity (ml)        | 50            |
| Blister              | Yes           |

## Description

**Description:** Airpress Thread Locker is designed for the locking and sealing of metal pipes and fittings. It cures when confined in the absence of air between close fitting metal surfaces and prevents loosening and leakage from shock and vibration Excellent resistance to motor oil, unleaded gas, ethanol, bio-diesel, etc.

**Application Instructions:** Wipe off any moisture, oil and dirt on the a rea to be treated. Shake well before using. Remove the cap. Apply a small amount to the required area/thread. Insert thread immediately to allow for thread locker to penetrate fully. After use, clean the nozzle before re-applying the cap. Before replacing the cap, ensure airspace remains in the bottle to prevent liquid from hardening.

**CAUTION:** May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

**Contains:** Polyglycol dimethacrylate, bisphenol a fumarate resin, cumene hydroperoxide. Keep out of reach of children. Avoid breathing dust/fume. Wear protective gloves/protective clothing/eye protection/face protection. If inhaled: Move to an area with fresh air and rest in a position comfortable for breathing. If in eyes: rinse cautiously with water for several minutes. Remove contact lenses as needed. Continue rinsing. If skin irritation or rash occurs seek medical attention.

