



# Compressed air filter A 2 1/2" F175 28000 l/min activated carbon 0.005 mg/m<sup>3</sup>

450200-A



## Product details

|                                  |   |
|----------------------------------|---|
| SKU                              | 450200-A                                  |
| EAN                              | 8712418395365                             |
| Weight (kg)                      | 7.300000                                  |
| Width (mm)                       | 164                                       |
| Height (mm)                      | 943                                       |
| Diameter Ø (mm)                  | 164                                       |
| Series                           | A   |
| Filter type                      | Activated carbon                          |
| Residual oil content (mg/m3)     | <0.005                                    |
| Replaceable cartridge            | Yes                                       |
| Housing material                 | Aluminium                                 |
| Element material                 | Borosilicate micro fibres (activ. carbon) |
| Air connection (")               | 2 1/2                                     |
| Working pressure (bar)           | 0 - 16                                    |
| Maximum pressure (bar)           | 16  |
| Flow rate (l/min)                | 28000                                     |
| Flow rate (m3/h)                 | 1680                                      |
| Minimum ambient temperature (°C) | 1.5                                       |
| Maximum ambient temperature (°C) | 45  |
| Type condensation drain          | Manual                                    |
| Pressure reducer                 | No  |
| Distance sensor                  | No  |

